



BK 119-270F-7,5

Compressore bicilindrico traino cinghia lubrificato, con motore trifase. Completo di pressostato elettromeccanico con protezione termica tramite relè termico.

Lubricated belt-driven two-cylinder compressor with three-phase engine. Electromechanical pressure switch with thermal relay protection.

Keilriemengetriebener Zweizylinder Kompressor mit 3-Phasen Motor. Elektromechanischer Druckschalter mit thermischem Auslöser.

Codice Code	Prodotto Product	L x D x H (cm)	kg	Lbs	tot.	Barcode
891BQ1A722	BK 113-270F-4	170 x 56 x 121	138	303,6	-	8017750195414
891Q1A722	BK 114-270F-5,5	170 x 56 x 121	138	303	-	8017750224855
891IT1A722	BK 119-270F-5,5	170 x 56 x 134	162,5	357,5	-	8017750193694
891IQ1A722	BK 119-270F-7,5	170 x 56 x 134	176	387,2	-	8017750193731
891BW1A722	BK 120-270F-10	176 x 54 x 140	211	465,2	-	8017750240879
883Q1A722	BK 114-500F-5,5	208 x 70 x 145	222	488,4	-	8017750224862
883IT1A722	BK 119-500F-5,5	208 x 70 x 145	222	488,4	-	8017750189437
883IQ1A722	BK 119-500F-7,5	208 x 70 x 145	235,5	518,1	-	8017750193052
883BW1A722	BK 120-500F-10	208 x 70 x 145	259	571	-	8017750164885

Code	Product	Volt/Ph	kW	HP	Model	l/min.	m ³ /h	c.f.m.	bar	p.s.i.	R.P.M.	n°	n°	dB(A)	LwA	L x D x H (cm)	kg	Lbs
------	---------	---------	----	----	-------	--------	-------------------	--------	-----	--------	--------	----	----	-------	-----	----------------	----	-----

BISTADIO TRIFASE FISSI STATIONARY DOUBLE-STAGE THREE-PHASE			STATIONÄR DOPPELSTUFE 3 PHASIG																
270	891BQ1A722	BK 113-270F-4 •	400/3	3	4	BK113	430	25,8	15,2	10	145	1370	2	2	78	94	150 x 50 x 103	116,5	256,3
270	891Q1A722	BK 114-270F-5,5 •	400/3	4	5,5	BK114	580	34,8	20,5	10	145	1370	2	2	80	-	150 x 50 x 111	116,5	256
270	891IT1A722	BK 119-270F-5,5 •	400/3	4	5,5	BK119	674	40,4	23,8	10	145	920	2	2	79	-	150 x 50 x 111	133	293,2
270	891IQ1A722	BK 119-270F-7,5 •	400/3	4	7,5	BK119	840	50,4	29,7	10	145	1250	2	2	80	-	150 x 50 x 111	146,5	323
270	891BW1A722	BK 120-270F-10 •	400/3	7,5	10	BK120	1080	64,6	38,1	10	145	1100	2	2	82	-	150 x 50 x 115	176	388
500	883Q1A722	BK 114-500F-5,5 •	400/3	4	5,5	BK114	580	34,8	20,5	10	145	1370	2	2	80	-	195 x 60 x 125	188	414,5
500	883IT1A722	BK 119-500F-5,5	400/3	4	5,5	BK119	674	40,4	23,8	10	145	920	2	2	79	-	195 x 60 x 125	188	414,5
500	883IQ1A722	BK 119-500F-7,5	400/3	5,5	7,5	BK119	840	50,4	29,7	10	145	1250	2	2	80	-	195 x 60 x 125	201,5	444,2
500	883BW1A722	BK 120-500F-10 •	400/3	7,5	10	BK120	1080	64,6	38,1	10	145	1100	2	2	82	-	195 x 60 x 128	225	496



BK 119-500F-5,5 TA

Compressore bicilindrico traino cinghia lubrificato. Con teleavviatore.

Lubricated belt-driven two-cylinder compressor with three-phase engine and remote control supplied.

Keilriemengetriebener Zweizylinder Kompressor mit 3-Phasen Motor und Fern-Ein/Aus-Kontakt.

Codice Code	Prodotto Product	L x D x H (cm)	kg	Lbs	tot.	Barcode
891Q1A922	BK 114-270F-5,5 TA	170 x 56 x 121	138	303	-	8017750224954
891IT1A922	BK 119-270F-5,5 TA	170 x 56 x 134	167,5	368,5	-	8017750202402
891IQ1A922	BK 119-270F-7,5 TA	170 x 56 x 134	181	398,2	-	8017750197821
891BW1A922	BK 120-270F-10 TA	176 x 54 x 140	216	476,1	-	8017750240886
883IT1A922	BK 119-500F-5,5 TA	208 x 70 x 145	227	499,4	-	8017750196916
883IQ1A922	BK 119-500F-7,5 TA	208 x 70 x 145	240,5	529,1	-	8017750197470
883BW1A922	BK 120-500F-10 TA	208 x 70 x 145	264	580,8	-	8017750241692
883BP5A922	BKV40/N-500F-15 TA	208 x 70 x 145	355	782,6	-	8017750248103
883BQ5A922	BKV40/N-500F-20 TA	208 x 70 x 145	368	811,3	-	8017750248110
893BQ5A922	BKV40/N-900F-20 TA	233 x 83 x 176	480	1058,2	-	8017750248127

Code	Product	Volt/Ph	kW	HP	Model	l/min.	m ³ /h	c.f.m.	bar	p.s.i.	R.P.M.	n°	n°	dB(A)	LwA	L x D x H (cm)	kg	Lbs
------	---------	---------	----	----	-------	--------	-------------------	--------	-----	--------	--------	----	----	-------	-----	----------------	----	-----

BISTADIO TRIFASE FISSI TELEAVVIATI STATIONARY STAR-DELTA DOUBLE-STAGE THREE-PHASE			STATIONÄR STERN-DREIECK DOPPELSTUFE 3 PHASIG																
270	891Q1A922	BK 114-270F-5,5 TA •	400/3	4	5,5	BK114	580	34,8	20,5	10	145	1370	2	2	80	-	150 x 50 x 111	116,5	256
270	891IT1A922	BK 119-270F-5,5 TA •	400/3	4	5,5	BK119	674	40,4	23,8	10	145	920	2	2	79	-	150 x 50 x 111	138	304,2
270	891IQ1A922	BK 119-270F-7,5 TA •	400/3	5,5	7,5	BK119	840	50,4	29,7	10	145	1250	2	2	79	-	150 x 50 x 111	151,5	334
270	891BW1A922	BK 120-270F-10 TA •	400/3	7,5	10	BK120	1080	64,6	38,1	10	145	1100	2	2	82	-	150 x 50 x 115	181	399
500	883IT1A922	BK 119-500F-5,5 TA •	400/3	4	5,5	BK119	674	40,4	23,8	10	145	920	2	2	79	-	200 x 60 x 125	193	425,5
500	883IQ1A922	BK 119-500F-7,5 TA •	400/3	5,5	7,5	BK119	840	50,4	29,7	10	145	1250	2	2	79	-	200 x 60 x 125	206,5	455,2
500	883BW1A922	BK 120-500F-10 TA •	400/3	7,5	10	BK120	1080	64,7	38,2	10	145	1100	2	2	82	-	200 x 60 x 128	230	506
500	883BP5A922	BKV40/N-500F-15 TA •	400/3	11	15	BKV40/N	1850	110	65,4	10	145	1080	4-V	2	88	-	200 x 60 x 130	320	705,5
500	883BQ5A922	BKV40/N-500F-20 TA •	400/3	15	20	BKV40/N	2500	150	88,3	10	145	1370	4-V	2	88	-	200 x 60 x 130	334	736,3
900	893BQ5A922	BKV40/N-900F-20 TA •	400/3	15	20	BKV40/N	2500	150	88,3	10	145	1370	4-V	2	88	-	212 x 80 x 155	434	956,8